

# CUTTING TOOL V320-AS-S

Part no: 72633200



#### **FORCE**

24 kN

### **PERFORMANCE WITH 5.0 AH BATTERY**

approx. 150 cycles

#### **FEATURES**

- Universial tool for almost every applications up to Ø 32 mm - not suitable for steel.
- Also suitable for Class 5 and Class 6 conductors according to IEC 60228 (VDE 0295).
- Blade changes not required. Consistent cuts in any processing sequence.
- Single-handed operation and with LED workspace light.

### **APPLICATION**

Cutting of power cables and underground cables as well as round material.

#### **SPECIFICATIONS**

Cable material / Conductor size and Diameter	Aluminum			
	Cutting (class 1, 2)	up to Ø 32 mm (max. 4x150 mm² re/rm)		
	Round bar	up to Ø 15 mm		
	Copper			
	Cutting (class 1, 2)	up to Ø 32 mm (max. 4x120 mm² re/rm)		
	Cutting (class 5, 6)	up to Ø 32 mm (max. 1x120 mm²)		
	Cutting (J-Y(St)Y 0,6 mm²)	up to Ø 32 mm		
	Round bar	up to Ø 15 mm		
Force	24 kN			
Opening Width	32 mm			
Battery Voltage	18 V (compatible with Makita)			
Weight	2,4 kg			
Dimensions* L x B x H	456 x 80 x 116 mm			
Cutting Head	open, 180° rotable			
Shape	Inline			

<sup>\*</sup> Supplied in a lightweight plastic case (battery and charger not included).



## CUTTING TOOL V320-AS-S

Part no: 72633200

### **INDUSTRIES**

Electrical engineering / Control cabinet construction / eMobility services, transformer construction, solar technology, grounding technology, Telecommunications, energy suppliers

#### **ACCESSORIES**

Item	Туре	Description		Part no.
Li-ion Battery Makita 18 V*	BL1850B	Capacity: Weight: Charger: Charging time:	5,0 Ah 0,64 kg DC18RC 45 min (100 %)	79300115
Quick charger	DC18RC	Voltage: Frequency: Output voltage: Weight: Dimension (mm):	220 – 240 V 50 – 60 Hz 8 V 0,9 kg 156 x 190 x 84	79300120
Battery adapter BO	ADAP-BO-18V	Adapter compatible with Bosch (18V)		79300092
Battery adapter MI	ADAP-MI-18V	Adapter compatible with Milwaukee (18V)		79300093
Battery adapter DE	ADAP-DE-18V	Adapter compatible with Dewalt (18V)		79300094

<sup>\*</sup> Additionally, 18V Makita batteries can be used: BL1815N, BL1820B, BL1830B, BL1840B, BL1860B.